

Paracril OZO® 728M60

Polyvinyl Chloride + NBR

INSA

Message:

Description:

Pre-fluxed blend of nbr/Pvc containing 30% Pvc .

28% ban nbr base rubber

Good tensile properties

Good green strength

Good abrasion resistance

Good flame resistance

Excellent ozone resistance

Applications:

Wire & cable

Footwear

Extrusions

Coated fabrics

Belting

General Information	
Features	Flame Retardant
	Good Abrasion Resistance
	Good Green Strength
	Ozone Resistant
Uses	Belts/Belt Repair
	Coating Applications
	Fabrics
	Footwear
	Wire & Cable Applications

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.06	g/cm ³	ASTM D297
Mooney Viscosity (ML 1+4, 100°C)	55 to 65	MU	ASTM D1646
Ash Content	< 0.8	wt%	ASTM D5667
Volatile Matter	< 0.75	wt%	ASTM D5668

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

