Jampilen HP522J

Polypropylene Homopolymer

Jam Polypropylene Company

Message:

Jampilen HP522J is a new homopolymer grade designed for the production of biaxially oriented polypropylene films (BOPP) primarily on high speed BOPP lines. This grade is characterised by its very broad processing window, easy film stretchability, good optical properties and reliable film thickness profile. Jampilen HP522J is suitable for metallization, both as monolayer and in coextruded structures. It does not contain any slip or antiblocking agents and it is Calcium Stearate free. Typical applications are BOPP packaging films and Sheet for Solid Phase Thermoforming. Jampilen HP522J is suitable for food contact.

General Information					
Features	Good Processability				
	Good Stretchability				
	High Clarity				
	High Gloss				
	Homopolymer				
	Medium Flow				
	Metallizable				
	Opticals				
Uses	Bi-axially Oriented Film				
	Film				
	Food Packaging				
	Packaging				
	Sheet				
	Thermoformed Containers				
Processing Method	Bi-axially Oriented Film				
	Coextruded Film				
	Thermoforming				
Physical	Nominal Value	Unit	Test Method		
Density	0.900	g/cm³	ISO 1183		
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	3.0	g/10 min	ISO 1133		
Hardness	Nominal Value	Unit	Test Method		
Shore Hardness (Shore D)	69		ISO 868		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Modulus	1370	MPa	ISO 527-2/1		
Tensile Stress (Yield)	33.0	MPa	ISO 527-2/50		
Tensile Strain			ISO 527-2/50		
Yield	11	%			

Break	550	%	
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature (0.45 MI	Pa,		
Unannealed)	85.0	°C	ISO 75-2/B
Vicat Softening Temperature	154	°C	ISO 306/A50

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

