## Geon™ Vinyl Flexible R252BE

Polyvinyl Chloride + NBR

PolyOne Corporation

## Message:

Geon™ Vinyl Flexible R252BE is a Polyvinyl Chloride + NBR (PVC+NBR) product. It can be processed by coextrusion, extrusion, or injection molding and is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Typical application: Construction Applications. Primary characteristic: uv stabilized.

General Information			
Additive	Biocide		
	UV Stabilizer		
Features	UV Absorbing		
Uses	Flooring		
Forms	Pellets		
Processing Method	Coextrusion		
	Extrusion		
	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.29	g/cm³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 15 sec)	83		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength <sup>1</sup> (Break)	15.9	MPa	ASTM D638
Tensile Elongation <sup>2</sup> (Break)	350	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-32.2	°C	ASTM D746
Injection	Nominal Value	Unit	
Processing (Melt) Temp	193 to 204	°C	
Extrusion	Nominal Value	Unit	
Melt Temperature	177 to 182	°C	
NOTE			
1.	Type IV, 510 mm/min		
2.	Type IV, 510 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

