

# SolVin 561SF

Polyvinyl Chloride Copolymer  
INOVYN

Message:

Vinylchloride-vinylacetate copolymer made by suspension polymerisation.  
This resin has been especially developed for automotive mastics.

APPLICATION  
Filler copolymer for plastisols.

General Information			
Features	Copolymer		
Uses	Automotive Applications		
Processing Method	Plastisol		
Physical	Nominal Value	Unit	Test Method
K-Value	61.0		ISO 1628-2
Vinyl Acetate Content	> 6.0	wt%	Internal Method
Sieve Analysis			ISO 1624
Mean diameter	40.0	µm	
Retained on 0.090 mm sieve	< 1.0	%	
Volatile Matter	< 0.30	%	ISO 1269

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT