

# Beamset EM-92

Polyurethane  
Arakawa Chemical Industries, Ltd.

Message:

This resin is a photo-curable resin that quickly and three-dimensionally cures by radical polymerization that occurs with electron beam (EB) or ultraviolet ray (UV) irradiation. This resin has been used widely for various applications.

Type:

Urethane acrylate emulsion

Characteristics:

Emulsion type

Excellent hardness

Good flexibility

Use:

Coatings

General Information		
Features	Good Flexibility	
	High Hardness	
Uses	Coating Applications	
Appearance	Milky White	
Additional Information	Nominal Value	Unit
Functionality	4.00	
Non-Volatile Content	40	%
Uncured Properties	Nominal Value	Unit
Viscosity (25°C)	0.070 to 0.15	Pa·s

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

  
WECHAT