

Sylvin 2906-85C Clear

Polyvinyl Chloride
Sylvin Technologies Incorporated

Message:
Sylvin 2906-85C Clear Is A Vinyl Compound Formulated With FDA Sanctioned Ingredients For Extrusion Or Injection Molding Applications.

General Information			
Agency Ratings	FDA Unspecified Rating		
Appearance	Clear/Transparent		
Processing Method	Extrusion		
	Injection Molding		

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.29	g/cm ³	ASTM D792

Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore C, 10 sec)	85		ASTM D2240

Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	22.8	MPa	ASTM D638
Tensile Elongation (Break)	230	%	ASTM D638

Elastomers	Nominal Value	Unit	Test Method
Tear Strength	140	kN/m	ASTM D624

Thermal	Nominal Value	Unit	
Melting Temperature	177 to 191	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China


WECHAT