

SOLARENE H635

High Impact Polystyrene
Dongbu Hannong Chemical

Message:

SOLARENE H635 is a High Impact Polystyrene product. It is available in Asia Pacific or Europe. Primary characteristic: flame rated.

General Information			
Forms	Pellets		
Thermal	Nominal Value	Unit	Test Method
RTI Elec			UL 746
1.59 mm	50.0	°C	
3.17 mm	50.0	°C	
RTI Imp			UL 746
1.59 mm	50.0	°C	
3.17 mm	50.0	°C	
RTI Str			UL 746
1.59 mm	50.0	°C	
3.17 mm	50.0	°C	
Electrical	Nominal Value		Test Method
Arc Resistance			ASTM D495
1.59 mm	PLC 7		
3.17 mm	PLC 7		
Comparative Tracking Index (CTI)			UL 746
1.59 mm	PLC 5		
3.17 mm	PLC 5		
High Amp Arc Ignition (HAI)			UL 746
1.59 mm	PLC 3		
3.17 mm	PLC 3		
High Voltage Arc Tracking Rate (HVTR)			UL 746
1.59 mm	PLC 0		
3.17 mm	PLC 0		
Hot-wire Ignition (HWI)			UL 746
1.59 mm	PLC 3		
3.17 mm	PLC 3		
Flammability	Nominal Value		Test Method
Flame Rating			UL 94
1.59 mm, ALL	HB		
3.17 mm, ALL	HB		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any

infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

