

# Pujie CPE-135C

Chlorinated Polyethylene

Zhanhua Pujie Chemical Technology Co.,Ltd

## Message:

This product is a random and saturated thermoplastic resin with minimal residual crystal and lowest molecule weight . It has very good processing flowing property and can be blended with ABS, PC, PE, PP and PVC in any ratio. Especially recommended for Flame Retardant ABS.

General Information	
Features	Low molecular weight
	Impact resistance, good
	Workability, good
	Good liquidity
	Good toughness
Uses	Mixing
	Plastic modification

Physical	Nominal Value	Unit	Test Method
Chlorine Content	31.0 - 33.0	wt%	
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	< 75		ISO 7619
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (Break)	> 6.00	MPa	ISO 37
Tensile Elongation (Break)	> 700	%	ISO 37
Thermal	Nominal Value	Unit	
Heat of Fusion	2.00	J/g	
Volatiles		%	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT