

NYLOY® CM-5000 8045B1

Polyamide 6

Nytex Composites Co., Ltd.

Message:

NYLOY®CM-5000 8045B1 is a polyamide 6 (nylon 6) material. This product is available in North America or Asia Pacific.

NYLOY®The main features of CM-5000 8045B1 are:

flame retardant/rated flame

Conductivity

Flame Retardant

General Information			
UL YellowCard	E135714-101407110		
Features	Conductivity		
	Heat conduction		
	Flame retardancy		
Appearance	Black		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.34	g/cm ³	ASTM D792
Molding Shrinkage			ASTM D955
Flow	0.40	%	ASTM D955
Transverse flow	0.75	%	ASTM D955
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	63.7	MPa	ASTM D638
Tensile Elongation (Break)	1.3	%	ASTM D638
Flexural Modulus	10800	MPa	ASTM D790
Flexural Strength	98.1	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C, 3.18 mm)	25	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	195	°C	ASTM D648
Thermal Conductivity			ASTM E1461
-- ¹	4.5	W/m/K	ASTM E1461
-- ²	15	W/m/K	ASTM E1461
Electrical	Nominal Value	Unit	Test Method
Surface Resistivity	1.0E+5	ohms	IEC 61340-4-1
Flammability	Nominal Value	Unit	Test Method
Flame Rating (3.2 mm)	V-0		UL 94
NOTE			
1.	Through-plane		
2.	In-plane		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

