SABIC® EPDM 626

Ethylene Propylene Diene Terpolymer

Saudi Basic Industries Corporation (SABIC)

Message:

SABIC® EPDM 626 is a high ethylene and low ENB grade produced by solution polymerization using metallocene catalyst. It has a tailored molecular weight distribution. This product is available in pellet form. Characteristics. Compared to typical narrow MWD grades SABIC® EPDM 626 is designed for: Better physical properties Improved mixing and mill handling Improved calenderability Better oil retention Reduced cure bloom in compounds Typical applications. Sheeting goods Roofing membranes and water proofing systems This product is not intended for and must not be used in any pharmaceutical/medical applications.

General Information			
Uses	Composite		
	Membrane		
	Sheet		
Forms	Particle		
Processing Method	Composite		
Physical	Nominal Value	Unit	Test Method
Mooney Viscosity (ML 1+4, 125°C)	67	MU	ASTM D1646
Ethylene Content	69.0	wt%	ASTM D3900
Ethylidene Norbornene (ENB) Content	2.8	wt%	ASTM D6047

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

