

# Evermore PUR SA-2260L

Polyurethane

Evermore Chemical Industry Co., Ltd.

Message:

Evermore PUR SA-2260L is a Polyurethane product. It is available in Asia Pacific. Typical application: Adhesives/Tapes. Primary characteristic: good adhesion.

General Information			
Features	Cleanable		
	Good Adhesion		
Uses	Adhesives		
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (100% Strain)	0.981 to 2.94	MPa	ASTM D412
Tensile Strength (Yield)	> 19.6	MPa	ASTM D412
Tensile Elongation (Break)	> 300	%	ASTM D412
Fill Analysis	Nominal Value	Unit	Test Method
Melt Viscosity (25.0°C)	12.0 to 15.0	Pa·s	ASTM D3835
Additional Information	Nominal Value	Unit	Test Method
Non-Volatile Content	58 to 62	%	
Solvents	DMF, TOL, MEK		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT