Hostacom HKC 465T

Polypropylene Homopolymer LyondellBasell Industries

Message:

"Hostacom" HKC 465T is a 20 % mineral filled polypropylene homopolymer containing post industrial scrap. It combines a good flowability with a high stiffness. The grade has been specifically designed for non visible and not colour matched structural IT and duct parts.

General Information	
Filler / Reinforcement	Mineral,20% Filler by Weight
Recycled Content	Yes
Features	Good Flow
	High Stiffness
	Homopolymer
Uses	Automotive Applications
	Automotive Under the Hood

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.05	g/cm³	ASTM D792, ISO 1183
Melt Mass-Flow Rate (MFR)			
230°C/2.16 kg	12	g/10 min	ASTM D1238
230°C/2.16 kg	10	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	23.0	MPa	ASTM D638
Flexural Modulus			
	2200	MPa	ASTM D790
Secant : 23°C	2200	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact			
23°C	35	J/m	ASTM D256
23°C	2.5	kJ/m²	ISO 180/1A

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519 Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

