

DynaMix™ 475-AFR

Low Density Polyethylene

Polymer Dynamix

Message:

DynaMix™ 475-AFR is a masterbatch containing a 2:1 blend of decabromodiphenylethane and antimony trioxide in a low density polyethylene carrier. This combination is recommended to be used in polyethylene and compatible systems at levels of 5 to 40%. Other loading levels and ratios are available upon request.

Features:

- Low Let Down Ratio
- Good dispersion for better physical properties and increased impact strength
- Non-Blooming
- Good processability

Applications:

- Films and Sheets
- Injection molding
- Compounding
- Profile Extrusion

General Information		
Features	Dispersible	
	Good Impact Resistance	
	Good Processability	
	Low Density	
	Non-Blooming	
Uses	Film	
	Masterbatch	
	Sheet	
Appearance	White	
Processing Method	Injection Molding	
Flammability	Nominal Value	Test Method
	V-2	
	V-1	
Flame Rating	V-0	UL 94

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

