

Softflex® 7503 Black

Thermoplastic Elastomer

Network Polymers, Inc.

Message:

Softflex® 7503 Black is a Thermoplastic Elastomer (TPE) product. It is available in North America. Typical application: Engineering/Industrial Parts.

General Information			
Uses	Overmolding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.03	g/cm³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness ¹ (Shore A)	75		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Strength (Break)	13.1	MPa	ASTM D638
Tensile Elongation (Break)	500	%	ASTM D638
Tear Strength	52.5	kN/m	ASTM D624
Additional Information	Nominal Value		
Overmold Bonding	ABS, PC and Nylon		
NOTE			
1.	Instantaneous		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT