

# HIFOR Xtreme® SC74849

Linear Low Density Polyethylene  
Westlake Chemical Corporation

## Message:

WESTLAKE HIFOR Xtreme Polyethylene SC74849 is a high strength linear low density polyethylene designed for blown file extrusion. This resin contains no slip, no anitblock, and polymer processing aid. Films produced with this resin exhibit extreme toughness, with excellent gloss and clarity for a product of this density. Features of this resin include high stiffness and high ultimate tensile strength.

General Information			
Features	High Gloss		
	High Stiffness		
	High Strength		
	High Tensile Strength		
	Medium Clarity		
	Ultra High Toughness		
Uses	Food Packaging		
	Packaging		
Agency Ratings	FDA 21 CFR 177.1520		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Density	0.925	g/cm <sup>3</sup>	ASTM D4883
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	0.55	g/10 min	ASTM D1238
Films	Nominal Value	Unit	Test Method
Secant Modulus			ASTM D882
1% Secant, MD	386	MPa	
1% Secant, TD	510	MPa	
Tensile Strength			ASTM D882
MD : Break	50.3	MPa	
TD : Break	39.3	MPa	
Tensile Elongation			ASTM D882
MD : Break	950	%	
TD : Break	1000	%	
Dart Drop Impact	60	g	ASTM D1709
Optical	Nominal Value	Unit	Test Method
Gloss (45°)	70		ASTM D2457
Haze	6.5	%	ASTM D1003

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any

infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

