

ALKAMIX™ MB-6009

Unspecified
Marplex Australia Pty. Ltd.

Message:

ALKAMIX™ MB-6009 is an Antiblock Masterbatch formulated with an antiblock additive concentration of 15 percent. ALKAMIX™ MB-6009 can be added to polyethylene during extrusion to reduce the blocking tendency of film, particularly where minimum blocking tendency is required. The level may vary according to desired properties, however the recommended addition level is between 1 and 3 percent. The maximum level of addition of ALKAMIX™MB-6009 based on both good manufacturing practice and to ensure conformance to the requirements to the United States Food and Drug Administration Regulations CFR21 is 6.5 percent, when added to a polyethylene formulation free of any antiblock additives. The suitability of finished articles manufactured using this material as a component, and the observance of given limitations, must be verified by the converter for each application to ensure compliance with all relevant regulations. An overall migration limit may apply to the finished article.

General Information			
Additive	Antiblock (15%)		
Uses	Masterbatch		
Physical	Nominal Value	Unit	Test Method
Density	0.920	g/cm³	ASTM D1505
Injection	Nominal Value	Unit	
Processing (Melt) Temp	< 200	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT