

# Guang Sung PVC GPMD80

Rigid Polyvinyl Chloride

Guang Sung Plastics (GSPL)

Message:

Guang Sung PVC GPMD80 is a Rigid Polyvinyl Chloride product. It can be processed by coextrusion or injection molding and is available in Asia Pacific. Typical application: Coating Applications. Primary characteristic: rohs compliant.

General Information	
Uses	Coating Applications
RoHS Compliance	RoHS Compliant
Forms	Pellets
Processing Method	Coextrusion Injection Molding

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.32	g/cm³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	80		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	49.2	MPa	ASTM D638
Tensile Elongation (Break)	> 100	%	ASTM D638
Flexural Modulus	2550	MPa	ASTM D790
Flexural Strength	69.6	MPa	ASTM D790

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519  
Phone: +86 13424755533  
Email: sales@su-jiao.com  
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

