

GELAST GTT-4

Thermoplastic Elastomer

Guang Sung Plastics (GSPL)

Message:

GELAST GTT-4 is a Thermoplastic Elastomer (TPE) product. It can be processed by injection molding and is available in Asia Pacific. Applications of GELAST GTT-4 include sporting goods, automotive, consumer goods, handles and household applications.

Characteristics include:

RoHS Compliant

Clarity

General Information			
Features	Good Colorability High Clarity		
Uses	Automotive Applications Handles Household Goods Sporting Goods Toys Water Sports Equipment		
RoHS Compliance	RoHS Compliant		
Appearance	Clear/Transparent		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.890	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 5 sec)	40		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus - 100% Secant	0.667	MPa	ASTM D638
Tensile Strength	8.14	MPa	ASTM D638
Tensile Elongation (Break)	760	%	ASTM D638
Additional Information	Nominal Value	Unit	Test Method
Tension Strength	20.8	kN/m	ASTM D624

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

