Fluoraz 790

Polytetrafluoroethylene

Greene, Tweed & Co.

Message:

This product is only available as a finished part, please contact Green, Tweed & Co. to discuss part availability, 215-216-9521.

General Information			
Uses	Aerospace Applications		
	Automotive Applications		
	Hydraulic Applications		
	Pressurized Containers		
	Pump Parts		
	Seals		
Forms	Pellets		
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	26.3	MPa	ASTM D638
Tensile Elongation (Break)	130	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (100% Strain)	21.9	MPa	ASTM D412

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

%

ASTM D395

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

21

Tel: +86 21 5895 8519

Compression Set

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

