

Sumiliteresin® PR-54624 I

Phenolic
SBHPP

Message:

SUMILITERESIN® PR-54624 I is NBR modified phenolic resin powder. It is generally applied for disc pad, brake lining and clutch facing.

Characteristics

SUMILITERESIN® PR-54624 I is a powder novolac type phenolic resin which contained about 15% NBR modified, hexamine about 9% and short Gel time. By this properties, it is good to improve friction coefficient, processability, and flexibility. By these kinds of characteristics, it will be suitable to manufacture soft, flexible, low noise and good feeling of braking of friction.

General Information		
Features	Rapid solidification crystal point	
	Good flexibility	
	Soft	
Appearance	White	
	Yellow	
Forms	Powder	
Physical	Nominal Value	Unit
Flow Length (125°C)	1.00 - 2.80	cm
Sieve Analysis - 150µm		%
Moisture Content		%
Uncured Properties	Nominal Value	Unit
Gel Time (165°C)	0.25 - 0.55	min

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China


WECHAT