

Sylvin 8390-93C Natural

Semi-Rigid Polyvinyl Chloride
Sylvin Technologies Incorporated

Message:

Sylvin 8390-93C Natural Is A Vinyl Compound Formulated For Semi Rigid Extruded Edge Band Applications That Need Lower Volatility And Better Chemical Resistance Than Our General Purpose Type.

General Information			
Features	Good chemical resistance		
	General		
Uses	Edge closure		
	Industrial application		
	General		
Appearance	Natural color		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.39	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shaw C	93		ASTM D2240
Shaw C, 10 seconds	93		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	20.0	MPa	ASTM D638
Tensile Strength (Break)	27.6	MPa	ASTM D638
Tensile Elongation (Break)	230	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method
Tear Strength	193	kN/m	ASTM D624
Thermal	Nominal Value	Unit	
Melting Temperature	182 - 196	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

