# ALCOM® PC 740/1.1 CF10 PTFE15

# Polycarbonate

### ALBIS PLASTIC GmbH

#### Message:

ALCOM® PC 740/1.1 CF10 PTFE15 is a Polycarbonate (PC) product filled with 10% carbon fiber. It is available in Asia Pacific, Europe, or North America. Applications of ALCOM® PC 740/1.1 CF10 PTFE15 include engineering/industrial parts, automotive and housings. Characteristics include: REACH Compliant RoHS Compliant Conductive Lubricated Wear Resistant

General Information				
Filler / Reinforcement	Carbon Fiber,10% Filler by Weight			
Additive	PTFE Lubricant (15%)			
Features	Electrically Conductive			
	Good Wear Resistance			
Uses	Automotive Applications			
	Bearings			
	Housings			
	Machine/Mechanical Parts			
Agency Ratings				
	EC 1907/2006 (REACH)			
RoHS Compliance	RoHS Compliant	11.2	Test Mathead	
Physical	Nominal Value	Unit	Test Method	
Density	1.32	g/cm³	ISO 1183	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Modulus	9200	MPa	ISO 527-2	
Tensile Stress (Break)	108	MPa	ISO 527-2	
Tensile Strain (Break)	1.7	%	ISO 527-2	
Flexural Modulus	8150	MPa	ISO 178	
Flexural Stress	154	MPa	ISO 178	
Impact	Nominal Value	Unit	Test Method	
Charpy Notched Impact Strength	7.0	kJ/m²	ISO 179/1eA	
Charpy Unnotched Impact Strength	29	kJ/m²	ISO 179/1eU	
Thermal	Nominal Value	Unit	Test Method	
Heat Deflection Temperature (1.8 MPa, Unannealed)	144	°C	ISO 75-2/A	
Vicat Softening Temperature	150	°C	ISO 306/B50	
Injection	Nominal Value	Unit		
Drying Temperature - Desiccant Dryer	100 to 120	°C		

Drying Time - Desiccant Dryer	2.0 to 3.0	hr	
Suggested Max Moisture	0.020	%	
Processing (Melt) Temp	310 to 330	°C	
Mold Temperature	80.0 to 130	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

# Recommended distributors for this material

# Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

