

Propilven J-758

Polypropylene Random Copolymer

Propilven, S.A.

Message:

Propilven J-758 grade is a random copolymer used in injection molding parts where high clarity and brightness is required, like food containers, video cases, among others.

Special Features:

High clarity and brightness

Good impact strength

Excellent organoleptic properties

Good de-molding properties

General Information			
Features	Food Contact Acceptable		
	Good Impact Resistance		
	Good Mold Release		
	Good Organoleptic Properties		
	High Clarity		
	Random Copolymer		
Uses	Food Containers		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR)	11	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	30.0	MPa	ASTM D638
Flexural Modulus	1000	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	70	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	85.0	°C	ASTM D648

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

