

ALCOM® PBT 700/1 GF30 PTFE15

Polybutylene Terephthalate

ALBIS PLASTIC GmbH

Message:

ALCOM® PBT 700/1 GF30 PTFE15 is a Polybutylene Terephthalate (PBT) product filled with 30% glass fiber. It is available in Asia Pacific, Europe, or North America. Applications of ALCOM® PBT 700/1 GF30 PTFE15 include engineering/industrial parts and automotive.

Characteristics include:

REACH Compliant

RoHS Compliant

High Stiffness

Lubricated

Wear Resistant

General Information			
Filler / Reinforcement	Glass Fiber,30% Filler by Weight		
Additive	PTFE Lubricant (15%)		
Features	Good Wear Resistance		
	High Stiffness		
Uses	Automotive Applications		
	Bearings		
	Gears		
	Machine/Mechanical Parts		
	Wheels		
Agency Ratings	EC 1907/2006 (REACH)		
RoHS Compliance	RoHS Compliant		
Physical	Nominal Value	Unit	Test Method
Density	1.65	g/cm ³	ISO 1183
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	10400	MPa	ISO 527-2
Tensile Strain (Break)	2.8	%	ISO 527-2
Flexural Modulus	9300	MPa	ISO 178
Flexural Stress	200	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength	9.0	kJ/m ²	ISO 179/1eA
Charpy Unnotched Impact Strength	50	kJ/m ²	ISO 179/1eU
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature (1.8 MPa, Unannealed)	210	°C	ISO 75-2/A
Vicat Softening Temperature	200	°C	ISO 306/B50
Injection	Nominal Value	Unit	
Drying Temperature			

Circulation Dryer	100 to 120	°C
Desiccant Dryer	100 to 120	°C
Drying Time		
Circulation Dryer	4.0 to 8.0	hr
Desiccant Dryer	2.0 to 4.0	hr
Processing (Melt) Temp	250 to 270	°C
Mold Temperature	80.0 to 120	°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

