

TAFMER™ BL2481M

Polyalphaolefin
Mitsui Chemicals, Inc.

Message:

TAFMER™ BL2481M, 1-butene based polymer, is a specialty olefinic resin designed to improve heat seal behavior of Polypropylene (PP) based film.

General Information			
Features	Butene comonomer		
	Good heat sealability		
Uses	Films		
	Plastic modification		
Agency Ratings	EU Unspecified Rating		
	FDA not rated		
Forms	Particle		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR)			ASTM D1238
190°C/2.16 kg	4.0	g/10 min	ASTM D1238
230°C/2.16 kg	9.0	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	47		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	200	MPa	ASTM D638
Tensile Strength (Break)	40.0	MPa	ASTM D638
Tensile Elongation (Break)	580	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-24.0	°C	ASTM D746
Melting Temperature	58.0	°C	Internal method

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT