

Lusin® Clean 1010

Thermoplastic

Chem-Trend L.P.

Message:

Ready-to-use Purging Compound for Screw, Barrel, Nozzle and Hot-runner of Injection Moulding Machines Processing Polymethylmethacrylate

Benefits

Especially dedicated for the cleaning of injection moulding machines processing polymethylmethacrylates (PMMA)

Economical due to low consumption

No smell during application

No contamination of the following parts

Removes residues and encrustations

Suitable for use on hot-runner systems

No generation of milky traces

Description

Lusin® Clean 1010 is a ready to use purging compound that is specially developed for the processing of PMMA. The purging compound consists of high quality thermoplastic resins as well as highly efficient cleaning additives and does not contain abrasives. The product is completely miscible with PMMA and does not generate any milky traces.

Lusin® Clean 1010 is suitable for colour and material change as well as for removal of black spot contaminations and carbon residues especially on transparent parts. Lusin® Clean 1010 can be used at processing temperatures up to 300°C (572°F).

Typical Properties

Appearance : Yellowish granules

General Information	
Additive	Unspecified additive
Uses	Cleaning compound
Appearance	Yellow
Forms	Particles

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

