

# Axiall PVC 8540

Flexible Polyvinyl Chloride

Axiall Corporation

## Message:

General purpose, flexible PVC compound recommended for extrusion or molding applications.

General Information	
Features	General Purpose
	Good Flexibility
Uses	General Purpose
Forms	Pellets
Processing Method	Extrusion
	Injection Molding

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.21	g/cm <sup>3</sup>	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	54		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus - 100% Secant	2.41	MPa	ASTM D638
Tensile Strength	7.58	MPa	ASTM D638
Tensile Elongation (Yield)	400	%	ASTM D638
Thermal	Nominal Value	Unit	
Melting Temperature	163	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT