

# Novamid® 2020A

Polyamide 66/6 Copolymer

DSM Engineering Plastics

## Message:

Novamid® 2020A is a Polyamide 66/6 Copolymer (Nylon 66/6) material. It is available in Asia Pacific for extrusion.

General Information			
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	1.13	g/cm <sup>3</sup>	ISO 1183
Water Absorption (Equilibrium, 23°C, 50% RH)	2.8	%	ISO 62
Viscosity Number	183	cm <sup>3</sup> /g	ISO 307
Thermal	Nominal Value	Unit	Test Method
Melting Temperature <sup>1</sup>	200	°C	ISO 11357-3
NOTE			
1.	10°C/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

