

# Diamond GPPS GP-525

General Purpose Polystyrene

Diamond Polystyrene

Message:

DIAMOND GP-500N & GP-525 are General Purposes Polystyrene having excellent clarity and gloss. They are available in Blue tint and have good dimensional stability at High temperature.  
GP-525 Blue Tinted, Excellent Clarity, Good Flow, Low Volatility (below 1000 ppm)

General Information			
Features	Good Dimensional Stability		
	Good Flow		
	Good Moldability		
	Good Strength		
	Good Surface Finish		
	High Clarity		
	High Gloss		
Uses	Appliance Components		
	Audio Tapes		
	Containers		
	Cups		
	General Purpose		
	Household Goods		
	Lighting Fixtures		
	Toys		
Appearance	Clear - Blue Tint		
	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	
Specific Gravity	1.04	g/cm <sup>3</sup>	
Melt Mass-Flow Rate (MFR) (230°C/1.2 kg)	7.0	g/10 min	
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	40.7	MPa	ASTM D638
Tensile Elongation (Break)	2.0	%	ASTM D638
Flexural Modulus	68.6	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	16	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method


Deflection Temperature Under Load (0.45 MPa, Unannealed)	90.0	°C	ASTM D648
Vicat Softening Temperature	95.0	°C	ASTM D1525

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519  
 Phone: +86 13424755533  
 Email: sales@su-jiao.com  
 No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT