# Hyundai EP Matt MF502L/Natural

### Polyolefin

HYUNDAI EP Co., Ltd.

#### Message:

Hyundai EP Matt MF502L/Natural is a Polyolefin product. It is available in Asia Pacific. Applications of Hyundai EP Matt MF502L/Natural include coating applications and packaging. Primary characteristic: low gloss.

General Information			
Features	Low Gloss		
	Soft		
Uses	Food Packaging		
	Laminates		
	Paper Coatings		
Appearance	Natural Color		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Apparent Density	0.57	g/cm³	Internal Method
Melt Mass-Flow Rate (MFR) (230°C/2.16			
kg)	4.5	g/10 min	ASTM D1238
Moisture Content	0.050	wt%	Internal Method
Black Spot <sup>1</sup>	0.00	count/g	Internal Method
Fish Eye <sup>2</sup>	4.00		Internal Method
Optical	Nominal Value	Unit	Test Method
Yellowness Index	3.0	YI	Internal Method
NOTE			
1.	2.5 grams		
2.	ea/600 cm²		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519 Phone: +86 13424755533 Email: sales@su-jiao.com No. 215, Lianhe North Road, Fengxian District, Shanghai, China

