# **DJSilicone NE-250**

#### Silicone

### DONGJUE SILICONE (NANJING) CO., LTD

#### Message:

This product could be put into basic processing after adding vulcanizator DCBP. And it may not need second vulcanization when technical conditions properly controlled. The formed product has the following properties: very good high and low temperature resistance, corona and arc resistance, and electric insulation. It is suitable for different kinds of electric wire and cable, jacket rubber tubes and parts for electrical insulator, heat-resistant seals, irregular shaped and foam strips.

General Information					
Features	Arc Resistant				
	Electrically Insulating				
	High Heat Resistance				
	Low Temperature Resistant				
Uses	Foam				
	Seals				
	Tubing				
	Wire & Cable Applications				
Appearance	Clear/Transparent				
	White				
Processing Method	Extrusion				
Physical	Nominal Value	Unit	Test Method		
Density	1.13 to 1.23	g/cm³	ASTM D1505		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness			ASTM D2240		
Shore A <sup>1</sup>	50 to 54				
Shore A <sup>2</sup>	48 to 52				
Elastomers	Nominal Value	Unit	Test Method		
Tensile Set			ASTM D412		
3	< 14	%			
4	< 12	%			
Tensile Strength <sup>5</sup> (Yield)	> 8.00	MPa	ASTM D412		
Tensile Elongation			ASTM D412		
Break <sup>6</sup>	> 380	%			
Break <sup>7</sup>	> 440	%			
Tear Strength	> 20.0	kN/m	ASTM D624		
Electrical	Nominal Value	Unit	Test Method		
Volume Resistivity	> 3.0E+14	ohms·cm	ASTM D257		

Dielectric Strength	> 20	kV/mm	ASTM D149
NOTE			
1.	For Tube		
2.	For Line		
3.	For Line		
4.	For Tube		
5.	For Line		
6.	For Tube		
7.	For Line		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

