

# ELASTOSIL® R 6225

Silicone

Wacker Chemie AG

## Message:

Silicone Rubber, RTV-2

Gaskets, Mechanical and Plant Engineering

cylinder head gasket, Automotive & Transportation

General Information			
Uses	Coating Applications		
Processing Method	Compression Molding Press Molding		
Uncured Properties	Nominal Value	Unit	Test Method
Color	Colorless		
Density	1.00	g/cm <sup>3</sup>	DIN 51757
Viscosity	3.0	Pa · s	Brookfield
Cured Properties	Nominal Value	Unit	Test Method
Shore Hardness (Shore A)	45		DIN 53505
Tensile Strength	5.00	MPa	DIN 53504
Tensile Elongation at Break	130	%	DIN 53504

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT