

ExxonMobil™ LDPE LD 252

Low Density Polyethylene Resin

ExxonMobil Chemical

Message:

LD 252 is a high-purity low-density polyethylene extrusion coating grade, specially developed to meet environmental requirements to reduce smoke emitted during plastic conversion. This grade has: low volatilization grade, reduced smoke emitted during high temperature extrusion (reduced by up to 20% compared with standard low density polyethylene), good shrinkage/drafting balance, reduced edge trim and thus reduced waste. -Good isolation performance, especially for water vapor, such as for single-piece packaging purposes (sugar, salt, etc.), good sensory performance, odorless and tasteless.

General Information			
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	3.8	g/10 min	ASTM D1238
Legal statement			

有关潜在食品接触应用合规信息(例如:FDA,EU,HPFB),请与埃克森美孚化工客户服务代表联系.本产品不宜在医疗应用中使用,亦不应在任何此类应用中使用

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

