

LG PVC PB1302

Polyvinyl Chloride Copolymer

LG Chem Ltd.

Message:

PB1302, homopolymer made from micro-suspension seeded polymerization, is a low-viscosity PVC resin with a pseudo-plastic flow property in processing range. It can be used for casting leather sheet, sheets made by knife coating and roll coating.

Main Applications:

Conveyor belt, Non-foaming products , General purpose grade for coated layer

General Information			
Features	Good Flow		
	Homopolymer		
	Low Viscosity		
Uses	Coating Applications		
	Sheet		
Physical	Nominal Value	Unit	Test Method
Apparent Density	0.31 to 0.41	g/cm ³	ASTM D1895
K-Value	70.0		ISO 1628-2
Viscosity			
B.F	5.00 to 35.0	Pa·s	ASTM D1824
S.V	> 240.00	g/10 min	ASTM D1823
Degree of Polymerization (30°C)	1200 to 1300		JIS K6720-2
Volatiles - 1 hr (110°C)	< 0.30	%	ASTM D3030

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

