

Nylene® BX3WQ662

Polyamide 6

Custom Resins Group

Message:

NYLENE® BX3WQ662X is a standard viscosity, heat stabilized, special nylon polymer, made specifically for wire jacketing. Provides excellent performance in applications that require a combination of toughness, abrasion resistance and chemical resistance. UL listed and meeting the requirements of UL 83 for wire jacketing.

General Information		
Additive	Heat Stabilizer	
Features	Good Abrasion Resistance	
	Good Chemical Resistance	
	Good Toughness	
	Heat Stabilized	
Uses	Wire & Cable Applications	
	Wire Jacketing	
Agency Ratings	UL 83	
Physical	Nominal Value	Unit
Moisture Content	< 0.12	%
Relative Viscosity ¹ (20°C)	2.65 to 2.95	
Copper Content	< 35	ppm
NOTE		
1.	96% Sulphuric Acid	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT