Borseal™ TD220BF

Polypropylene Terpolymer

Borealis AG

Message:

Borseal TD220BF is a C2/C4 terpolymer

This grade is designed for sealing layers of oriented and non oriented films

General Information			
Additive	Antiblock		
Features	Antiblocking		
	Excellent Printability		
	Good Heat Seal		
	Low Temperature Heat Sealability		
	Low to No Odor		
	Low to No Taste		
	Low VOC		
	MedWide Molecular Weight Distrib.		
	Metallizable		
	Opticals		
	Recyclable Material		
Uses	Film		
	Food Packaging		
	Laminates		
	Non-oriented Film		
	Oriented Film		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	6.0	g/10 min	ISO 1133
Films	Nominal Value	Unit	Test Method
Seal Initiation Temperature ¹ (30 μm)	108	°C	Internal Method
Thermal	Nominal Value	Unit	Test Method
Melting Temperature	132	°C	ISO 11357-3
NOTE			
1.	2 N		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

