

E-Pos 562

Epoxy; Epoxide

Epocat Nederland BV

Message:

E-Pos 562 is a low viscosity bisphenol A-based epoxy resins which is diluted with a bifunctional reactive diluent.

Product applications

E-Pos 562 is used in combination with amine-based curing agents in the formulation of two-pack ambient curing systems. E-Pos 562 enables the formulation of systems exhibiting high chemical resistance. This resin can be used in civil engineering applications such as self-leveling floorings, trowellable floorings or mortars and in the formulation of solventfree paints resisting to chemical agents.

General Information		
Features	Good Chemical Resistance	
	Low Viscosity	
Uses	Flooring	
	Paint	
Agency Ratings	EC 1907/2006 (REACH)	
Physical	Nominal Value	
Gardner Color	< 1.00	
Epoxy Equivalent	170 to 185	g/mol
Uncured Properties	Nominal Value	Unit
Solids Content	100	%
Density (20°C)	1.10	g/cm ³
Viscosity (25°C)	0.90 to 1.3	Pa·s

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT