

BB-AMIDE 5012

Polyamide

BB Resins S.r.l.

Message:

BB-AMIDE 5012 is a low viscosity polyamido-imidazoline resin.

The main characteristics of BB-AMIDE 5012 are:

long pot-life

low viscosity

good compatibility with epoxy resins

BB-AMIDE 5012 is useful for formulating floorings, castings, electrical encapsulation and adhesive for wood field.

General Information	
Features	Low Viscosity
Uses	Adhesives
	Flooring
Appearance	Amber
Forms	Liquid
Processing Method	Casting
	Encapsulating

Physical	Nominal Value	
Gardner Color	< 10.0	
Brookfield Viscosity (25°C)	100 to 500	mPa · s
Active Content	100	%
Amine Value	350 to 400	mg KOH/g
Mixing Ratio - with liquid epoxy resin	50	%
Thermoset	Nominal Value	Unit
Pot Life ¹ (25°C)	250	min

NOTE		
1.	on 200 g mass with liquid epoxy resin	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co., Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT