

# Sylvin 8754-60FUV Orange 576

Flexible Polyvinyl Chloride  
Sylvin Technologies Incorporated

Message:

Sylvin 8754-60FUV Orange 576 Is A Flexible Vinyl Compound Formulated For Low Gloss Applications. This Compound Contains An Antimicrobial And A UV Stabilizer.

General Information			
Additive	Antibacterial (fungicide)		
	UV stabilizer		
Features	Gloss, low		
	General		
Uses	Industrial application		
	General		
Appearance	Orange		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.22	g/cm³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shaw A	60		ASTM D2240
Shaw A, 10 seconds	60		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	9.31	MPa	ASTM D638
Tensile Elongation (Break)	400	%	ASTM D638
Thermal	Nominal Value	Unit	
Melting Temperature	154 - 166	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT