

Yanshan PE LD615

Low Density Polyethylene
SINOPEC Beijing Yanshan Petrochemical

Message:

Yanshan PE LD615 is a Low Density Polyethylene product. It can be processed by injection molding and is available in Asia Pacific. Typical application: Additive/Masterbatch.

General Information			
Uses	Masterbatch		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.922	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR)	15	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	7.00	MPa	ASTM D638
Tensile Elongation (Break)	75	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	85.0	°C	ASTM D1525

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT