

# Bapolan® PS6078-G

High Impact Polystyrene  
Bamberger Polymers, Inc.

## Message:

Bapolan 6078-G is a colored, high impact polystyrene.

General Information			
Features	General Purpose		
Uses	General Purpose		
Appearance	Unspecified Color		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (200°C/5.0 kg)	8.0	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	20.7	MPa	ASTM D638
Flexural Modulus - 1% Secant	2070	MPa	ASTM D790A
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	85	J/m	ASTM D256

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

