Pujie CM40

Chlorinated Polyethylene

Zhanhua Pujie Chemical Technology Co.,Ltd

Message:

CM40, Very high viscosity, high chlorine content, good flame retardancy and oil resistance

General Information		
Features	Oil resistance	
	Viscosity, High	
	Flame retardancy	
Uses	Films	
	Strap	
	Wire and cable applications	
	Pipe	
Physical	Nominal Value	Unit
Apparent Density	> 0.50	g/cm³
Mooney Viscosity (ML 1+4, 125°C)	80 - 90	MU
Chlorine Content	39.0 - 41.0	wt%
Hardness	Nominal Value	Unit
Durometer Hardness (Shore A)	< 60	
Mechanical	Nominal Value	Unit
Tensile Strength	> 8.50	MPa
Tensile Elongation (Break)	> 650	%
Thermal	Nominal Value	Unit
Heat of Fusion		J/g
Impurities		pcs/50 g
Volatiles		%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519 Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

