

# BJB Epoxy TC-4207 A/B

Epoxy; Epoxide

BJB Enterprises, Inc.

## Message:

TC-4207 A/B is a buff-colored epoxy adhesive with a smooth, paste-like consistency. It has been used primarily for bonding wood, metal and plastics. The TC-4207 A/B has a semi-paste consistency providing a more vertical hang than its sister product designated TC-4206 A/B.

General Information			
Features	General Purpose		
Uses	Adhesives		
	General Purpose		
Forms	Liquid		
Physical	Nominal Value	Unit	Test Method
Water Absorption (24 hr)	2.0	%	ASTM D570
Viscosity	Semi-paste		
Gel Time	1.8	hr	
Tack Free Time (25°C)	6.0 to 8.0	hr	
Work Time <sup>1</sup> (25°C)	1.0	hr	
Cure Time - Full (25°C)	1.7	day	
Lap Shear <sup>2</sup>	13.8	MPa	ASTM D1002
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	65 to 70		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Compressive Strength	68.9	MPa	ASTM D695
Thermoset	Nominal Value	Unit	Test Method
Thermoset Components			
Part A	Mix Ratio by Weight: 100		
Part B	Mix Ratio by Weight: 100		
Shelf Life	52	wk	
NOTE			
1.	1 lb mass		
2.	Aluminum to Aluminum, etched		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

