

Durez® 33840

Phenolic

Sumitomo Bakelite North America, Inc.

Message:

Durez 33840 is a novolak phenolic resin in flake form.

Durez 33840 is recommended for use in foundry molds or cores.

Contains a wax for easy mold release.

Contains a plasticizer for increased thermal shock resistance.

General Information			
Additive	Plasticizer		
	Wax		
Features	Good Mold Release		
	Plasticized		
Uses	Molds/Dies/Tools		
Forms	Flakes		
Physical	Nominal Value	Unit	Test Method
Thickness - Flake	1.27	mm	Internal Method
Thermoset	Nominal Value	Unit	Test Method
Thermoset Mix Viscosity ¹ (150°C)	675	cP	Internal Method
NOTE			
1.	Molten		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT