

# Lucopren® SB 1551-60S

Styrene Butadiene Styrene Block Copolymer

Lucobit AG

## Message:

Lucopren® SB 1551-60S is a Styrene Butadiene Styrene Block Copolymer (SBS) product. It is available in Europe.

General Information			
Appearance	Natural Color		
Forms	Granules		
Physical	Nominal Value	Unit	Test Method
Density <sup>1</sup>	0.900 to 0.940	g/cm <sup>3</sup>	DIN 53479
Melt Mass-Flow Rate (MFR) (190°C/5.0 kg)	8.0	g/10 min	ISO 1133
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore A)	57 to 63		DIN 53505
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress			DIN 53504-S2
100% Strain	2.10	MPa	
300% Strain	3.40	MPa	
500% Strain	4.80	MPa	
Tensile Stress (Yield)	6.40 to 8.40	MPa	DIN 53504-S2
Tensile Elongation (Break)	730 to 930	%	DIN 53504-S2
Compression Set (23°C, 72 hr)	45 to 55	%	DIN 53517
NOTE			

1. Method A

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

