

# ELASTEL™ E78

Ethylene Propylene Diene Terpolymer

HELLENIC CABLES S.A.

## Message:

Description: EPDM based compound for the production of an elastic profile

Packaging: In carton boxes of approximately 400-500 kg

Use: Sealing of aluminum profiles, window frames, etc.

General Information		
Uses	Profiles	
Processing Method	Extrusion	
Physical	Nominal Value	Unit
Specific Gravity	1.33	g/cm <sup>3</sup>
Hardness	Nominal Value	Unit
Shore Hardness (Shore A)	67 to 71	
Extrusion	Nominal Value	Unit
Cylinder Zone 1 Temp.	60.0	°C
Cylinder Zone 2 Temp.	65.0	°C
Cylinder Zone 3 Temp.	65.0	°C
Head Temperature	70	°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

