# AZDEL™ SM10380

### Polypropylene

Azdel, Inc.

#### Message:

AZDEL SM10380 is a glass mat thermoplastic laminate based upon random oriented continuous fiber mat contained within polypropylene resin matrix. This composite material features high flow properties and a very homogeneous fiber distribution. This material is typically used for standard semi-structural applications and where high impact and stiffness are desired, and is usually used in sheet form (un-molded) in applications such as large-truck trailer scuff liners.

General Information				
Filler / Reinforcement	Long glass fiber, 38% fill	Long glass fiber, 38% filler by weight		
Appearance	Black			
Forms	Sheet			
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.17	g/cm³	ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Modulus	5140	МРа	ISO 527-2	
Tensile Stress (Yield)	79.0	МРа	ISO 527-2	
Tensile Strain (Break)	2.6	%	ISO 527-2	
Flexural Modulus	5140	МРа	ISO 178	
Flexural Stress	140	МРа	ISO 178	
Impact	Nominal Value	Unit	Test Method	
Instrumented Dart Impact (4.00 mm, To	otal 23.0	J	ASTM D3763	
Energy) Thermal	Nominal Value	Unit	Test Method	
		Offic	rest Metriod	
Deflection Temperature Under Load (1 MPa, Unannealed)	.8 154	°C	ASTM D648	
CLTE - Flow (-40 to 121°C)	2.3E-5	cm/cm/°C	ASTM D696	
Flammability	Nominal Value	Unit	Test Method	
Burning Rate	5.3	mm/min	ISO 3795	
Additional Information				

Basis Weight, Internal Test Method: 0.67 lbs/ft²Filler Content by Weight(ashing), Internal Test Method: 38 %Notched Izod Impact, ISO 180, 23°C, 4mm: 771 J/mSheet Thickness, Internal Test Method: 108 milsSpecific Gravity, ASTM D792, Laminated: 1.17

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519 Phone: +86 13424755533 Email: sales@su-jiao.com No. 215, Lianhe North Road, Fengxian District, Shanghai, China

