

HANWHA KL-31

Polyvinyl Chloride

Hanwha Chemical

Message:

Feature: High foam cell/fast gelling. Good for floor materials and foamed wall paper

Use: Wall paper, flooring, low melting temperature foaming agents and leathers

General Information			
Features	Foamable property		
	Rapid solidification crystal point		
Uses	Synthetic Leather		
	Floor Material		
	Foam		
Physical	Nominal Value	Unit	Test Method
Apparent Density	0.25 - 0.33	g/cm ³	ASTM D1895
Volatile Matter		%	ASTM D3030
Particle size-100Mesh(150μm) Sieve Pass%	100	%	Internal method
Brokfield viscosity-cps/6rpm			ASTM D1824
degree of polymerization			
DP	950 - 1050		JIS K6720-2
K-Value	66.0		DIN 53726
Additional Information	Nominal Value	Test Method	
Liquidity: Dilatant			

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

