

ELASTEL™ SBR 1102-S

Styrene Butadiene Rubber

HELLENIC CABLES S.A.

Message:

Description: SBR based compounds for inner sheaths of elastic power cables

Specifications: VDE 0250 Teil 813(1985) TYPE GM1b

Packaging: In carton boxes of approximately 400-1000 kg

Types of cables where it can be used: NSSHou, NTSCGEWou

General Information		
Uses	Wire & Cable Applications	
RoHS Compliance	RoHS Compliant	
Processing Method	Extrusion	
Physical	Nominal Value	Unit
Specific Gravity	1.40	g/cm ³
Extrusion	Nominal Value	Unit
Cylinder Zone 1 Temp.	50.0	°C
Cylinder Zone 2 Temp.	55.0	°C
Cylinder Zone 3 Temp.	55.0	°C
Head Temperature	60	°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT