

BCC Resins MB1100

Polyurethane

BCC Products Inc.

Message:

MB 1100 is an Olive colored rigid closed-cell polyurethane foam tooling and modeling board. MB 1100 is low density foam of approximately 10lbs/ft³ board. Easily cut using CNC machining equipment or by hand the MB 1100 is perfectly suited for temporary master models, architectural design models, foundry patterns as well as design verification and prototype tools.

General Information			
Features	Foamable		
	Good Abrasion Resistance		
	Good Dimensional Stability		
	Good Surface Finish		
	Low Density		
	Low Shrinkage		
	Machinable		
Uses	Aerospace Applications		
	Agricultural Applications		
	Automotive Applications		
	Foam		
	Modeling Material		
	Molds/Dies/Tools		
	Prototyping		
Appearance	Green		
Forms	Liquid		
Processing Method	Foam Processing		
	Machining		
Physical	Nominal Value	Unit	Test Method
Density	0.160	g/cm ³	ASTM D1505
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	20		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	2.41	MPa	ASTM D638
Flexural Strength	2.62	MPa	ASTM D790
Compressive Strength	1.93	MPa	ASTM D695
Thermal	Nominal Value	Unit	Test Method
Continuous Use Temperature	40.6 to 257	°C	ASTM D794
CLTE - Flow	5.9E-5	cm/cm/°C	ASTM D696

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

